



School Bus

Tech Specs



IdlePro® Alternators

System Voltage	12V
Temperature Rating	-40°C to 125°C
Diodes	12*
Lamp Driver	High or low side driver
Mounting	J180 Hinge Mount Pad Mount
Rotation	Clockwise
Weight	240-Amp, 22 lbs.
	3-Year/Unlimited Mileage



IdlePro Extreme® Alternators

System Voltage	12V
Temperature Rating	-40°C to 125°C
Diodes	12
Lamp Driver	High or low side driver
Mounting	J180 Hinge Mount Pad Mount
Rotation	Clockwise
Weight	280-Amp to 350-Amp, 39 lbs. 420-Amp, 40 lbs.
	4-Year/Unlimited Mileage





IdlePro® & IdlePro Extreme® Alternator Application Chart

PRESTOLITE #	AMP	SCHOOL BUS APPLICATION	TYPE OF MOUNTING
A160207 A160208	210	Min. loads for 2002 & earlier	Pad Mount J-180 Mount
A160203 A160204	240	Min. loads for 2007 & later 1 A/C load for 2002 & earlier	Pad Mount J-180 Mount
BLP4009	280	1 A/C load for 2007 & later	Pad Mount
BLP4002H	325	2 A/C loads for 2007 & later & other combinations	Pad Mount
BLP4004H	350	3 A/C, Extensive ADA Ride Share – Wheel Chair Lift.	Pad Mount
BLP4003	420	3 A/C, Extensive ADA Ride Share – Wheel Chair Lift.	Pad Mount

Output Curves

The alternator on a school bus spends the vast majority of its working life operating at very low speeds. Most school bus alternators usually operate at about 2,000 RPM and seldom get above 4,000 RPM. The only important rating is the amount of power that the alternator can produce while the engine is idling. Don't be misled by posted "maximum RPM ratings" that the unit and application will never be able to achieve.



* Check with your Prestolite representative for more details

†Delco Remy is a registered trademark of General Motors Corporation, licensed to BorgWarner PDS (Anderson) L.L.C. ††28SI and 38SI are registered trademarks of BorgWarner.

Contact Your Sales Representative Today!



School Bus

Tech Specs



PowerPro Extreme® 5 Starters



Engine Size	Up to 10L, 12V
Rotation	Clockwise
Mounting	SAE #1, SAE #3
Output	5kW
Flange	Fixed
Weight	21.5 lbs / 9.8 kg
Operating Temperature	-40°C to 125°C
	School Bus Applications, 3-Year/Unlimited Mileage

PowerPro Extreme 5 Starters

LEECE-NEVILLE	DESCRIPTION	TEETH	OCP	WARRANTY
M95301H	Cummins ISC/ISL, International DT466, DT530, DT570, Maxx Force 9&10	12	No	 School Bus Applications, 3-Year/ Unlimited Mileage
M95303H	Cummins ISB 6.7L	10	No	
M95307H	Cummins ISB 6.7L for Bluebird and other applications needing additional ground stud	10	No	
M95309H	Detroit Diesel DD5 and DD8	11	No	
M95312H	Cummins ISC/ISL for Bluebird and other applications needing additional ground stud	12	No	

Contact Your Sales Representative Today!

7585 Empire Drive • Florence, KY 41042 • (800) 354-0560 • www.IdleProExtreme.com

IdlePro, IdlePro Extreme, and PowerPro Extreme are registered trademarks or trademarks of Prestolite Electric Incorporated in the United States and certain other countries. All other trademarks mentioned are the property of their respective owners. Copyright © 2020 Prestolite Electric Incorporated. All rights reserved.

Learn more
@PrestoliteElectric

